



Pressure sensitive electric switch

Patent Number: ☐ GB2064873
Publication date: 1981-06-17
Inventor(s):
Applicant(s): EVENTOFF FRANKLIN NEAL
Requested Patent: ☐ DE3044384 
Application Number: GB19800037047 19801119
Priority Number (s): US19790097610 19791126; US19800110416 19800107; US19800135386 19800331; US19800140921 19800416; US19800140937 19800416
IPC Classification: H01H1/02; H01H13/52
EC Classification: B60C23/04C, H01H1/02B, H01H13/70B
Equivalents: AU544234, CA1153801, ☐ FR2470435, ☐ GB2134320, ☐ GB2134321, ☐ GB2134322, ☐ IT1143185, ☐ NL8006409, ☐ SE452925, ☐ SE8008205

Abstract

A pressure responsive electric switch has at least one pair of first (104) and second (112) conductors in spaced- apart relationship with at least one pressure sensitive resistive conductor (106, 114) is disposed in a position to interconnect the conductors when a force is applied. The invention may be incorporated in multiple touch switches having the conductors (220, 240) Figure 7 disposed side by side or stacked one above the other as in Figure 10 (not shown). The resistive conductor may be made from molybdenum disulphide particles with a resin binder and may include powdered carbon. 

Data supplied from the esp@cenet database - I2

BEST AVAILABLE COPY